



OOLV2.E472253
Lamps, Self-ballasted, Light-emitting-diode Type - Component

Page Bottom

Lamps, Self-ballasted, Light-emitting-diode Type - Component

[See General Information for Lamps, Self-ballasted, Light-emitting-diode Type - Component](#)

HYPERIKON INC

E472253

6255 Ferris Square, Ste A
 San Diego, CA 92121 USA

Self-Ballasted Lamps, LED Type, Model(s) 142000XY1 (^), 142000XY2 (^), 142000XY3 (^)

LED lamps - devices substituting for fluorescent lamps (Types B and C)

Model Dsg.	Rated Input	Lamp Type	Environment	Lamp Shape	Lamp Length	Lamp Diameter	Lamp Base	Elec Config	Mounting Orientation	Lamp Mass	Dimmable?	Eval for ROS?
HyperBR20-G24XX (a)												
	120-277V, 60 Hz	B	Damp	Other [a]	n/a	n/a	G24	-	Any	n/a	No	n/a
HyperBR30-G24XX (a)												
	120-277V, 60 Hz	B	Damp	Other [a]	n/a	n/a	G24	-	Any	n/a	No	n/a
HyperBR30-G24XX1 (a)												
	120-277V, 60 Hz	B	Damp	Other [a]	n/a	n/a	G24	-	Any	n/a	No	n/a
HyperBR40-G24XX (a)												
	120-277V, 60 Hz	B	Damp	Other [a]	n/a	n/a	G24	-	Any	n/a	No	n/a
HyperBR40-G24XX1 (a)												
	120-277V, 60 Hz	B	Damp	Other [a]	n/a	n/a	G24	-	Any	n/a	No	n/a
HyperPL-G24XX (a)												
	120-277V, 60 Hz	B	Damp	Other [a]	n/a	n/a	G24	-	Any	n/a	No	n/a
HyperPL-G24XX1 (a)												
	120-277V, 60 Hz	B	Damp	Other [a]	n/a	n/a	G24	-	Any	n/a	No	n/a
HyperPL-G24XX2 (a)												
	120-277V, 60 Hz	B	Damp	Other [a]	n/a	n/a	G24	-	Any	n/a	No	n/a

[a] Custom value or configuration. See UL report for details.

(a) - Where XX denotes the color temperature of LED, and it can be 22(2200K), 27(2700K), 30(3000K), 35(3500K), 40(4000K), 50(5000K), 60(6000K)

(^) - X indicates lamp base, Y indicates color temperature

Marking: Company name and model designation.

Last Updated on 2015-10-22

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".